



**MAXIMUM OPERATING TEMPERATURES**

**Applicable from 2012 05**

A quick reference guide only. Refer to Product Data sheets for more detailed information.

<b>Product Description</b>	<b>Maximum Operating Temperatures</b>
MH Series Pumps	-15°C to +110°C
MHQP Series Pumps	-15°C to +110°C
VR series Pumps	-15°C to +120°C
SR Series Pumps	-10°C to +90°C
CS Series Pumps	-5°C to +40°C
ISO Series Pump	-15°C to +85°C
FPS 4" TriSeal and SandHandler Series Pumps	49°C
ST Series pumps	60°C
FT Series Pumps	75°C
FS Series Pumps	75°C
4" Encapsulated Motors	30°C (60°C* derated)
6" Encapsulated Motors	30°C (60°C* derated)
8" Encapsulated Motors	30°C (60°C* derated)
4" Hi Temp 75C Oil Stripper Encapsulated Motors	75°C
6" DR56 Encapsulated Motors	50°C
6" Hi Temp 90C Encapsulated Motors	90°C
8" Hi Temp 75C Encapsulated Motors	75°C
6", 8", 10" Rewindable Motors, Standard PVC winding	25°C to 30°C
12" Rewindable Motors, Standard PVC winding	30°C
4" Oil Lubricated Motors	30°C

**For any items not noted or listed, please contact us at:**

**Toll Free AU: 1300 FRANKLIN (1300 372 655) or [feaustralia@fele.com](mailto:feaustralia@fele.com)**

. \* Refer to 50 Hz AIM manual for de-rating specifications.